Fas
ADVANCED
1050

MAIN FEATURES

7" Interface tablet
Interface enduser touchscreen customizeable with logos, videos. Programming iconographic easy and fast.

Intelligent lighting
Power LED at high efficiency with programmable energy saving function; delivery bin illuminated intermittently when product is delivered

Fas Cloud +
Management, programming, updates, cloning and Audit functions on site or from remote via Fas Cloud+

Double Glazed glass with high efficiency
Laminted glass with security and low emission to avoid fogging and condensation

Typical Configurations available
Up to 3 different zone temperatures (Snack/Drink/Food); Lateral air flow to avoid build up condensation (patented)

CO2 Cooling unit monobloc
Refrigeration unit charged with CO_2 (GWP=1) with inverter board to control to speed; Fast extraction due to the Slide in - Slide out system (patented)

D **Efficiency energy rating**

Fas
ADVANCED
1050

TECHNICAL FEATURES

Dimensions and finishing

Number of trays standard/maximum	6/7
Number of selections	Up to 70
Hieght - Width - Depth	1830 - 1050 - 790 mm
Footprint with door open	1810 mm
Weight	324 Kg
Aesthetic finishing	Anodized grey and black

Electrical data

Power supply	230/50-60 V/Hz
Rated power	450 W
Minimal internal temperature	3°C with health control

Amenities

Protocols	Executive/MDB
Digital Display Trays	Optional
Anti-theft bars	Optional
Easy Click system	Yes
Photocells product delivery	Yes
Pre-cooling compartment	Yes
WI-FI and bluetooth LE native	Yes